

## PERFORMANCE

Code

Rev

Issue Date

s	DLIDARIETÄ INTRAPRESA	FEATURES	Al-dop- 01	0	04/2013
1.	Unique identification	code of product type			C20T-R2T
2.	type, serie,batch number			C20	
3.	intended use of the p	product			Staircase may be used inside "A" En1990:2002 category buildings
4.	manufacturer				Solidarietà Intrapresa ONLUS Via campo dei fiori 3/b 47122 Forlì T.0543 722777 F.0543 722599 amministrazione@solidarietaintrapresa.it
5.	purchasing agent				None
6.	evaluation system and performance regularity check			System 1	
7.	regulation			ETAG 008-01 January 2002	
8.	served system	served system Ed. ITC served system N° 0970		Ed. ITC served system N° 0970	
9.	features declared				

Essential features	Performance	Regulation
DIMENSIONAL DETAILS		
Staircase diameter	Min 1100mm Max 1600mm	
Going Size	From 230mm to 390mm	
Riser	210mm and 230mm	
Number of treads every 360°	12	
Treads Thickness	40mm	ETAG 008-01
Handrail Height	Min 980mm to 1145mm	January 2002 Ed.
AIR TEMPERATURE FOR STAIRCASE USE	Min +5°C max +30°C	
RELATIVE HUMIDITY FOR STAIRCASE USE	Min 30% max 70%	
FIRE REACTION	irrelevant	
SLIPPERINESS	irrelevant	
IMPACT RESISTANCE	irrelevant	
SOUND-PROOF	irrelevant	
ENERGY-SAVING AND HEAT RETENTION	irrelevant	
DURABILITY *	50 years	

<sup>\*</sup> depends on respecting the usage precautions and general info showed inside the product specification heet.

The present statement of perormance is released under the exclusive responsabilitty of the manufacturer, as mentioned at point 4

The manufacturer

Fabrizio Amaducgi

Forlì, 05/05/2013

<sup>10.</sup> Features at points 1-2 are in compliance with declared features at point 9.