

features declared

PERFORMANCE FEATURES

Code

Rev

Issue Date

s	DLIDANIETĀ INTRAPRESA	FEATURES	Al-dop- 02	0	04/2013	
1.	Unique identification code of product type F20T-R2T					
2.	type, serie,batch number				F20	
intended use of the product				Staircase may be used inside "A"		
	5			En1990:2002 category buildings		
4.	. manufacturer			Solidarietà Intrapresa ONLUS		
					Via campo dei fiori 3/b 47122 Forlì	
					T.0543 722777 F.0543 722599	
					amministrazione@solidarietaintrapresa.it	
5.	purchasing agent			None		
6.	evaluation system and performance regularity check			System 1		
7.	regulation				ETAG 008-01 January 2002	
8.	served system	ved system Ed. ITC served system N° 0970			Ed. ITC served system N° 0970	

Essential features	Performance	Regulation	
DIMENSIONAL DETAILS			
Staircase diameter	Min 1100mm Max 1600mr	n	
Going Size	From 230mm to 390mm 210mm and 230mm		
Riser			
Number of treads every 360°	12	ETAG 008-01	
TTread Thickness (press-formet plate)	3mm		
Handrail Height	Min 980mm to 1145mm	January 2002 Ed.	
AIR TEMPERATURE FOR STAIRCASE USE	Min +5°C max +30°C		
RELATIVE HUMIDITY FOR STAIRCASE USE	Min 30% max 70%		
FIRE REACTION	irrelevant		
SLIPPERINESS	irrelevant		
IMPACT RESISTANCE	irrelevant		
SOUND-PROOF	irrelevant		
ENERGY-SAVING AND HEAT RETENTION	irrelevant		
DURABILITY *	50 years		

^{*} depends on respecting the usage precautions and general info showed inside the product specification heet.

10. Features at points 1-2 are in compliance with declared features at point 9.

The present statement of perormance is released under the exclusive responsabilitty of the manufacturer, as mentioned at point 4

The manufacturer

Fabrizio Amaducci

Forli, 05/05/2013