

PERFORMANCE

Code

Rev

Issue Date

		I LIN ONW WOL	i i	[issue Dute	
SOLIDA	RIETA INTRAPHESA	FEATURES	Al-dop- 03	0	04/2013	
1. Un	ique identification	code of product type			K20-R-GLE	
2. typ	type, serie,batch number				K20	
3. into	intended use of the product				Staircase may be used inside "A"	
					En1990:2002 category buildings	
4. ma	inufacturer				Solidarietà Intrapresa ONLUS	
					Via campo dei fiori 3/b 47122 Forlì	
					T.0543 722777 F.0543 722599	
	- <u>-</u>				amministrazione@solidarietaintrapresa.it	
5. pur	rchasing agent				None	
6. eva	evaluation system and performance regularity check				System 1	
7. reg	regulation				ETAG 008-01 January 2002	
8. ser	served system			Ed. ITC served system N° 0970		
	tures declared			· ,	La. 170 serven system N 0970	

Essential features	Performance	Regulation
<u>DIMENSIONAL DETAILS</u>		
Treads Width	Min 600mm Max 850mm	
Going Size	From 180mm to 250mm	
Treads Depth	260mm and 300mm	
Riser	Min 170mm max 235mm	
Tread Thickness	40mm	ETAG 008-01
Handrail Height	Min 970mm to 1170mm	January 2002 Ed.
AIR TEMPERATURE FOR STAIRCASE USE	Min +5°C max +30°C	,
RELATIVE HUMIDITY FOR STAIRCASE USE	Min 30% max 70%	
FIRE REACTION	irrelevant	
SLIPPERINESS	irrelevant	
IMPACT RESISTANCE	irrelevant	
SOUND-PROOF	irrelevant	
ENERGY-SAVING AND HEAT RETENTION	irrelevant	
DURABILITY * depends on respecting the usage precautions and general info sho	50 years	

^{10.} Features at points 1-2 are in compliance with declared features at point 9.

The present statement of perormance is released under the exclusive responsabilitty of the manufacturer, as mentioned at point 4

The manufacturer

Fabrizio Amaducci

Forlì, 05/2013