

PERFORMANCE FEATURES

Code Rev

Issue Date

\$	DLIDARIETÀ INTRAFRESA	FEATURES	Al-dop- 05	0	04/2013		
1.	Unique identification co	ode of product type			L20-2R-GLA		
2.	type, serie,batch num	ber			L20		
3.	intended use of the pro	oduct			Staircase may be used inside "A" En1990:2002 category buildings		
4.	manufacturer				Solidarietà Intrapresa ONLUS Via campo dei fiori 3/b 47122 Forlì T.0543 722777 F.0543 722599 amministrazione@solidarietaintrapresa.it		
5.	purchasing agent				None		
6.	evaluation system and	performance regularity check			System 1		
7.	regulation				ETAG 008-01 January 2002		
8.	served system				Ed. ITC served system N° 0970		
9.	features declared						

Essential features	Performance	Regulation
DIMENSIONAL DETAILS		
Treads Width	Min 500mm Max 1000mm	-
Going Size	From 200mm to 250mm	
Treads Depth	260mm and 310mm	
Riser	Min 160mm max 250mm	
Treads Thickness (press-formed plate)	40mm (plate thickness 3mm)	ETAG 008-01
Handrail Height	Min 970mm to 1170mm	January 2002 Ed.
AIR TEMPERATURE FOR STAIRCASE USE	Min +5°C max +30°C	
RELATIVE HUMIDITY FOR STAIRCASE USE	Min 30% max 70%	
FIRE REACTION	irrelevant	- -
SLIPPERINESS	irrelevant	
IMPACT RESISTANCE	irrelevant	
SOUND-PROOF	irrelevant	
ENERGY-SAVING AND HEAT RETENTION	irrelevant	
DURABILITY *	50 years	

^{*} depends on respecting the usage precautions and general info showed inside the product specification heet.

The present statement of perormance is released under the exclusive responsabilitty of the manufacturer, as mentioned at point 4

The manufacturer

Fabrizio Amaducci

Forlì, 05/05/2013

^{10.} Features at points 1-2 are in compliance with declared features at point 9.